



DENSOSEAL 16A

DESCRIPTION Densoseal 16A is a non setting, self supporting mastic which may be applied to wet surfaces and will seal ducts and conduits against ingress of gas and water. It complies with British Telecom Specification M212C. For sealing cable ducts, conduits and service entry pipes or sleeves particularly below ground level to prevent entry of gas or water into buildings. It may also be used for profiling mechanical joints on hot pipes to allow application of tapes.

COMPOSITION Firm mastic based on polybutene, fatty acids, mineral fillers, organic fibres and water displacing materials.

TYPICAL PROPERTIES	DATA
Colour	Pale yellow
Specific Gravity	1.73
Specific Volume	578cm ³ /kg
Flash Point	>150°C
Pressure Resistance	Withstands 35kPa (5 lb/in ²) air pressure for over 15 minutes. Withstands 20kPa (2 metre head) water pressure for over 60 minutes.
Adhesion	Adheres to wet or dry surfaces of the following: iron, steel, glazed earthenware, lead, brass, polythene and pvc
Temperature Range <i>For Application</i> <i>For Service</i>	0°C to 35°C -15°C to 100°C

PACKING	330mm x 40mm x 40mm. 8 x 1kg strips per carton Corrugated Strips 350mm x 60mm 100 x approx 160g strips per carton
----------------	--

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net