



DENSO OVERBANDING TAPE

DESCRIPTION A cold applied bituminous tape for surface sealing of open seams or cracks up to 5mm width in road pavements on secondary roads.

COMPOSITION A blend of polymer modified bitumen in tape form, protected by a disposable release film.

| TYPICAL PROPERTIES | DATA |
|---|------------------|
| Softening Point | 120°C |
| Resistance to Water, Acids, Alkalis and Salts | Excellent |
| Temperature Range for Application | 8°C to 45°C |
| Temperature Range for Service | -20°C to 80°C |
| Roll Length | 10m |
| Width | 30mm, 40mm, 50mm |
| Core Size | 76mm I.D. |
| Thickness | 1.9mm |

| | |
|---------|--|
| PACKING | 24 (30mm), 20 (40mm), 16 (50mm) rolls per carton |
|---------|--|

| | |
|--------------------|------------------|
| RECOMMENDED PRIMER | Densoband Primer |
|--------------------|------------------|

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net