

**DENSO FLASHING TAPE**

<b>DESCRIPTION</b>	A cold applied self adhesive aluminium backed flashing in tape form.
<b>USES</b>	Waterproofing of roof to wall and other building joints.
<b>COMPOSITION</b>	High melting point polymer bitumen adhesive laminated to a 40 micron aluminium/polyester laminate with grey weatherproof lacquer finish. The adhesive surface is protected by a release coated plastics film which is discarded during use.

TYPICAL PROPERTIES	TEST METHOD	DATA
<b>Breaking Strength</b>	ASTM D1000	4.5 N/mm
<b>Elongation @ break</b>	ASTM D1000	100%
<b>Adhesion Strength</b>	ASTM D1000	4.5 N/mm width
<b>Adheres to:</b>		Metal, concrete, brick, slate, tile painted wood, glass and rigid plastics
<b>Temperature Range</b> <i>For Application</i> <i>For Service</i>		5°C to 40°C 80°C (maximum short term)
<b>Roll Length</b>		10 metres minimum
<b>Thickness</b>		1.0mm
<b>Weight</b>		1.0 kg/m <sup>2</sup> average

<b>RECOMMENDED PRIMER</b>	Denso Flashing Tape Primer
---------------------------	----------------------------

**Important**

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom  
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net