



## DENSO HOTLINE TAPE

**DESCRIPTION** Cold applied conformable fabric based tape for the corrosion protection of pipes operating at elevated temperatures. Suitable for the protection of copper, iron or steel pipes above ground in ducts or set in concrete.

For below ground applications please refer to technical properties as a high temperature outerwrap is recommended.

**COMPOSITION** Non-rotting synthetic fibre fabric impregnated and coated with a compound based on petrolatum and synthetic polymers and having a clear plastics film backing.

TYPICAL PROPERTIES	DATA
<b>Colour</b>	Red/Brown
<b>Breaking Strength</b>	200 N/50mm minimum
<b>Elongation at Break</b>	15%
<b>Breakdown Voltage</b>	16 kV minimum per double layer
<b>Temperature Range</b>	
<i>For Application</i>	5°C to 50°C
<i>For Service</i>	110°C maximum
<b>Roll Length</b>	10m rolls
<b>Width</b>	50mm to 300mm
<b>Total Thickness</b>	1.4mm
<b>Weight</b>	1.44kg/m <sup>2</sup>

Note: For buried pipe applications a compatible high temperature Denso Glass Outerwrap Tape is recommended.

### Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom  
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net