



LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET

125 YEARS SERVICE TO INDUSTRY



REF: TDS141/01.12

DENSOSTRIP PRIMER

DESCRIPTION A fast drying bitumen based primer for all joint surfaces prior to the application of Densostrip flexible jointing compound to precast concrete units.

TYPICAL PROPERTIES	DATA
Non Volatile Content	60% w/w
Specific Gravity	0.94
Flash Point	23°C minimum
Coverage on Concrete	3-5m ² /litre
Drying Time	10-20 minutes
Application Temperature Range	0°C to 45°C

SURFACE PREPARATION	Joint surfaces shall be undamaged, clean and dry. Wire brush to remove dust, dirt and loose material.
----------------------------	---

APPLICATION	Apply one coat by brush. Use white spirit for cleaning.
--------------------	--

PACKING	5 litre and 25 litre metal containers
----------------	---------------------------------------

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548)

Winn & Coales (Denso) Ltd
Denso House, Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net