



## DENSYL MASTIC

**DESCRIPTION** Densyl Mastic is a cold applied self-supporting mastic for sealing, filling and caulking applications where a protective, waterproof and non-setting mastic is required. Suitable for application in a wide range of climatic conditions. It is specially recommended for duct sealing and around pipes and cables where they enter buildings to prevent the passage of water or gas. It is used for moulding around irregular profiles such as flanges, mechanical joints, and valves to provide a contour suitable for wrapping with anti-corrosion tapes e.g. Denso Tape, Densopol and Densoclad Tapes.

**COMPOSITION** Petrolatum compound containing inert siliceous fillers and vegetable fibres. It contains no volatile organic solvents.

TYPICAL PROPERTIES	DATA
Colour	Green/Brown
Specific Gravity	1.39
Specific Volume	720 cm <sup>3</sup> /kg
Flash Point	>180°C
Temperature Range For Application For Service	0°C to 70°C 90°C maximum

<b>PACKING</b>	3kg Blocks Extruded Rounds Strips 330mm long x 50mm diameter Extruded Triangular Strips 330mm long x 50mm x 50mm x 70mm
----------------	---

<b>RECOMMENDED PRIMER</b>	Where required use Denso Hi-Tack Primer
---------------------------	---

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom  
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net