



constructive solutions

Fosroc Primer 7E

Two-part primer primarily for sealants.

Description

Primer 7E is a two part high performance chemically active, non-toxic liquid for brush application to prime all concrete, stone, brickwork, timber and unglazed edges of ceramic tiles.

Advantages

- Easy to Apply
- Strong adhesion

Application

Empty the entire contents of the hardener tin into the base tin, replace base tin lid. Mix thoroughly until a homogeneous dispersion is achieved.

Apply one thin coat using a clean dry brush. Avoid over application of primer causing puddles in the bottom of the joint. The mixed sealant must be applied when the primer becomes tacky but not wet (typically between 5 - 20 minutes after application). If the primer dries, the joint surfaces must be re-primed before applying the sealant.

Cleaning

Clean equipment immediately after use with Fosroc Solvent 102.

Estimating

Supply

Primer 7E:	500 ml can
-------------------	------------

Coverage

Primer 7E:	8-10 m ² / ltr
-------------------	---------------------------

Storage

Shelf life

12 months if stored in the original unopened packs in a cool dry place. Do not store in direct sunlight.

Precautions

Health and safety

Primer 7E highly flammable liquid. Shall be stored away from heat. and shall not be used near a naked flame. Skin contact shall be avoided. Eye protection and impervious rubber or PVC gloves shall be worn. Splashes must be washed off immediately. Prolonged breathing of vapour shall be avoided.

Hands shall be washed thoroughly before eating or smoking. In the case of eye contact, medical attention shall be sought immediately.

Disposal

Dispose according to local authority regulations. Do not dispose down drains or into local waterways.

For further information on any of the above, please consult your local Fosroc office - as below.

Additional information

Flash point:	Primer 7E 23°C
Storage life:	12 months
Drying time:	20 to 60 mins.
Flash point - Fosroc Solvent 102:	33°C

For further info please contact your local Fosroc office.



Fosroc Jordan

Head Office
P.O Box 253,
King Abdullah II Industrial State
Sahab 11512, Jordan
www.fosroc.com

Important note:

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Services, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification of information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it.

Regional Offices:

Amman-Khalda Offices: Tel: (06) 535 9562
Amman-Sahab Factory: Tel: (06) 402 2665
Aqaba Showroom: Tel: (03) 205 0061

email: enquiryjordan@fosroc.com

Fax: (06) 535 9563
Fax: (06) 402 9475
Fax: (03) 205 0062